

DOCCT0000059-02

DIECI

DIECI



**DIECI REANGE
CONSTRUCTION**

Dieci S.r.l.
Via E. Majorana, 2-4
42027 Montecchio Emilia (RE) ITALY
info@dieci.com

dieci.com

**DIECI REANGE
CONSTRUCTION**



dieci.com



TELESCOPIC HANDLERS



| APOLLO 26.6 | DEDALLUS 28.7 - GD | DEDALLUS 30.7 - GD | DEDALLUS 28.9 - GD | DEDALLUS 30.9 - GD | ZEUS 40.7 - GD | ZEUS 38.8 - GD | ZEUS 38.10 - GD | ZEUS 35.11 - GD | ZEUS 40.13 - GD | ICARUS 40.14 - GD | ICARUS 40.17 - GD | ICARUS 50.18 - GD | SAMSON 50.8 VS EVO2 - GD | SAMSON 65.8 VS EVO2 - GD | SAMSON 60.9 VS EVO2 - GD | SAMSON 75.10 | PIVOT40 | PIVOT50 | PIVOT60 | PIVOT70 | PIVOT80 | PIVOT90 |
|--------------------|--------------------|--------------------|--------------------|--------------------|------------------------|------------------------|------------------------|------------------------|------------------------|------------------------|---------------------|---------------------|--------------------------|--------------------------|--------------------------|---------------------|--------------------|--------------------|--------------------|--------------------|--------------------|--------------------|
| Kubota | Kubota | Kubota | Kubota | Kubota | Kubota | Kubota | Kubota | Kubota | Kubota | Kubota | Kubota | Kubota | FPT | FPT | FPT | FPT | Kubota | Kubota | Kubota | Kubota | FPT | FPT |
| 55 kW (74 HP) | 79,5 kW (107 HP) | 79,5 kW (107 HP) | 79,5 kW (107 HP) | 79,5 kW (107 HP) | 55,4 kW (74 HP) | 55,4 kW (74 HP) | 55,4 kW (74 HP) | 55,4 kW (74 HP) | 55,4 kW (74 HP) | 85,1 kW (114 HP) | 85,1 kW (114 HP) | 85,1 kW (114 HP) | 103 kW (138 HP) | 103 kW (138 HP) | 103 kW (138 HP) | 103 kW (138 HP) | 36,5 kW (49 HP) | 54,6 kW (73 HP) | 54,6 kW (73 HP) | 83,5 kW (112 HP) | 96 kW (129 HP) | 103 kW (138 HP) |
| 30 km/h (18,6 mph) | 40 km/h (24,9 mph) | 40 km/h (24,9 mph) | 40 km/h (24,9 mph) | 40 km/h (24,9 mph) | 30 km/h (18,6 mph) | 30 km/h (18,6 mph) | 30 km/h (18,6 mph) | 30 km/h (18,6 mph) | 30 km/h (18,6 mph) | 38 km/h (23,6 mph) | 38 km/h (23,6 mph) | 27 km/h (16,8 mph) | 40 km/h (24,9 mph) | 40 km/h (24,9 mph) | 40 km/h (24,9 mph) | 40 km/h (24,9 mph) | 22 km/h (13,7 mph) | 30 km/h (18,6 mph) | 40 km/h (24,9 mph) | 40 km/h (24,9 mph) | 36 km/h (22,4 mph) | 40 km/h (24,9 mph) |
| 2600 kg (5732 lb) | 2900 kg (6393 lb) | 3000 kg (6614 lb) | 3000 kg (6614 lb) | 2900 kg (6393 lb) | 3000 kg (6614 lb) | 4000 kg (8818 lb) | 3800 kg (8378 lb) | 3500 kg (7716 lb) | 4000 kg (8818 lb) | 4000 kg (8818 lb) | 4000 kg (8818 lb) | 5000 kg (11023 lb) | 4000 kg (8818 lb) | 6500 kg (14330 lb) | 6000 kg (13228 lb) | 7500 kg (16535 lb) | 1800 kg (3968 lb) | 2250 kg (4960 lb) | 2250 kg (4960 lb) | 3000 kg (6614 lb) | 3500 kg (7716 lb) | 4100 kg (9039 lb) |
| 5,68 m (18,6 ft) | 6,35 m (20,8 ft) | 6,35 m (20,8 ft) | 6,65 m (21,8 ft) | 6,65 m (21,8 ft) | 7,2 m (23,6 ft) | 7,6 m (24,9 ft) | 9,6 m (31,5 ft) | 10,6 m (34,8 ft) | 12,5 m (41 ft) | 13,40 m (44 ft) | 16,40 m (53,8 ft) | 17,80 m (58,4 ft) | 7,70 m (25,3 ft) | 7,70 m (25,3 ft) | 8,60 m (28,2 ft) | 9,65 m (31,7 ft) | 4,00 m (13,1 ft) | 4,70 m (15,4 ft) | 4,70 m (15,4 ft) | 5,00 m (16,4 ft) | 5,20 m (17,1 ft) | 5,7 m (18,7 ft) |
| 4125 mm (162,4 in) | 4720 mm (185,8 in) | 4720 mm (185,8 in) | 4755 mm (187,2 in) | 4755 mm (187,2 in) | 4971 mm (195,7 in) | 5435 mm (214 in) | 4995 mm (196,7 in) | 5270 mm (207,5 in) | 5970 mm (235 in) | 6200 mm (244,1 in) | 6250 mm (246,1 in) | 6900 mm (271,7 in) | 5023 mm (197,8 in) | 5023 mm (197,8 in) | 5373 mm (211,5 in) | 5910 mm (232,7 in) | 5035 mm (198,2 in) | 5400 mm (212,6 in) | 5400 mm (212,6 in) | 5520 mm (217,3 in) | 5895 mm (232,1 in) | 6440 mm (253,5 in) |
| 1850 mm (72,8 in) | 2060 mm (81,1 in) | 2060 mm (81,1 in) | 2060 mm (81,1 in) | 2060 mm (81,1 in) | 2290 mm (90,2 in) | 2290 mm (90,2 in) | 2290 mm (90,2 in) | 2290 mm (90,2 in) | 2290 mm (90,2 in) | 2390 mm (94,1 in) | 2390 mm (94,1 in) | 2440 mm (96,1 in) | 2375 mm (93,5 in) | 2375 mm (93,5 in) | 2390 mm (94,1 in) | 2380 mm (93,7 in) | 1753 mm (69 in) | 1880 mm (74 in) | 1880 mm (74 in) | 2250 mm (88,6 in) | 2250 mm (88,6 in) | 2400 mm (94,5 in) |
| 1950 mm (76,8 in) | 2040 mm (80,3 in) | 2040 mm (80,3 in) | 2040 mm (80,3 in) | 2040 mm (80,3 in) | 2210 mm (87 in) | 2410 mm (94,9 in) | 2410 mm (94,9 in) | 2410 mm (94,9 in) | 2410 mm (94,9 in) | 2530 mm (99,6 in) | 2530 mm (99,6 in) | 2650 mm (104,3 in) | 2545 mm (100,2 in) | 2545 mm (100,2 in) | 2545 mm (100,2 in) | 2490 mm (98 in) | 2490 mm (98 in) | 2490 mm (98 in) | 2690 mm (105,9 in) | 2680 mm (105,5 in) | 2680 mm (105,5 in) | 2790 mm (109,8 in) |
| 5000 kg (11023 lb) | 6500 kg (14330 lb) | 6500 kg (14330 lb) | 6680 kg (14727 lb) | 6680 kg (14727 lb) | 8000 kg (17637 lb) | 8300 kg (18298 lb) | 8550 kg (18850 lb) | 8850 kg (19511 lb) | 9850 kg (21716 lb) | 10900 kg (24030 lb) | 12260 kg (27029 lb) | 14750 kg (32518 lb) | 10560 kg (23281 lb) | 11300 kg (24912 lb) | 11500 kg (25353 lb) | 12100 kg (26676 lb) | 4950 kg (10913 lb) | 6020 kg (13272 lb) | 6020 kg (13272 lb) | 7150 kg (15763 lb) | 8000 kg (17637 lb) | 9800 kg (21605 lb) |
| 12x16,5" | 400/70x20" | 400/70x20" | 400/70x20" | 400/70x20" | 400/70-24" (16/70-24)" | 400/70-24" (16/70-24)" | 400/70-24" (16/70-24)" | 400/70-24" (16/70-24)" | 400/70-24" (16/70-24)" | 400/70-24" (16/70-24)" | 440/70x24" | 440/70x24" | 440/70x24" | 18-22,5" | 18-22,5" | 18-22,5" | 18x22,5" | 405/70x20" | 405/70x20" | 405/70x20" | 15,5x25" | 600/55-26,5" |

TRUCK MIXER



| AB N 2400 | AB N 2400T | AB L 3500 | AB L 3500T | AB L 3500 CCS | AB L 4700 | AB L 4700 T | AB L 4700 CCS | AB F 7000 | AB F 7000 T | AB F 7000 CCS |
|--------------------|--------------------|--------------------|--------------------|--------------------|--------------------|--------------------|--------------------|--------------------|--------------------|--------------------|
| Lombardini | Lombardini | Perkins | Perkins | Perkins | Perkins | Perkins | Perkins | Perkins | Perkins | Perkins |
| 36,6 kW (49 HP) | 36,6 kW (49 HP) | 85,9 kW (115 HP) | 85,9 kW (115 HP) | 85,9 kW (115 HP) | 85,9 kW (115 HP) | 85,9 kW (115 HP) | 85,9 kW (115 HP) | 100 kW (134 HP) | 100 kW (134 HP) | 100 kW (134 HP) |
| 27 km/h (16,8 mph) | 27 km/h (16,8 mph) | 27 km/h (16,8 mph) | 27 km/h (16,8 mph) | 27 km/h (16,8 mph) | 27 km/h (16,8 mph) | 27 km/h (16,8 mph) | 27 km/h (16,8 mph) | 27 km/h (16,8 mph) | 27 km/h (16,8 mph) | 27 km/h (16,8 mph) |
| 270 L (71,3 gal) | - | 500 L (132,09 gal) | - | 500 L (132,09 gal) | 600 L (158,5 gal) | - | 600 L (158,5 gal) | 600 L (158,5 gal) | - | 600 L (158,5 gal) |
| 1,7 m³ (60 ft³) | 1,7 m³ (60 ft³) | 2,5 m³ (88 ft³) | 2,5 m³ (88 ft³) | 2,5 m³ (88 ft³) | 3,5 m³ (124 ft³) | 3,5 m³ (124 ft³) | 3,5 m³ (124 ft³) | 5,0 m³ (177 ft³) | 5,0 m³ (177 ft³) | 5,0 m³ (177 ft³) |
| 4495 mm (177 in) | 4400 mm (173,2 in) | 5030 mm (198 in) | 4955 mm (195,1 in) | 5030 mm (198 in) | 5290 mm (208,3 in) | 5290 mm (208,3 in) | 5290 mm (208,3 in) | 6100 mm (240,2 in) | 6100 mm (240,2 in) | 6475 mm (254,9 in) |
| 1960 mm (77,2 in) | 1960 mm (77,2 in) | 2370 mm (93,3 in) | 2370 mm (93,3 in) | 2370 mm (93,3 in) | 2400 mm (94,5 in) | 2400 mm (94,5 in) | 2400 mm (94,5 in) | 2370 mm (93,3 in) | 2370 mm (93,3 in) | 2370 mm (93,3 in) |
| 2620 mm (103,1 in) | 2620 mm (103,1 in) | 2915 mm (114,8 in) | 2880 mm (113,4 in) | 2880 mm (113,4 in) | 3140 mm (123,6 in) | 3140 mm (123,6 in) | 3140 mm (123,6 in) | 3040 mm (119,7 in) | 3040 mm (119,7 in) | 3040 mm (119,7 in) |
| 4000 kg (8818 lb) | 4000 kg (8818 lb) | 5900 kg (13007 lb) | 5900 kg (13007 lb) | 5900 kg (13007 lb) | 6700 kg (14771 lb) | 6400 kg (14110 lb) | 6700 kg (14771 lb) | 7400 kg (16314 lb) | 7400 kg (16314 lb) | 7400 kg (16314 lb) |
| 10,5x18" | 10,5x18" | 12,5x18" | 12,5x18" | 12,5x18" | 405/70x20" | 405/70x20" | 405/70x20" | 405/70R24" | 405/70R24" | 405/70R24" |

DUMPER



| AB N 2400 | AB N 2400T | AB L 3500 | AB L 3500T | AB L 3500 CCS | AB L 4700 | AB L 4700 T | AB L 4700 CCS | AB F 7000 | AB F 7000 T | AB F 7000 CCS |
|--------------------|--------------------|--------------------|--------------------|--------------------|--------------------|--------------------|--------------------|--------------------|--------------------|--------------------|
| Lombardini | Lombardini | Perkins | Perkins | Perkins | Perkins | Perkins | Perkins | Perkins | Perkins | Perkins |
| 36,6 kW (49 HP) | 36,6 kW (49 HP) | 85,9 kW (115 HP) | 85,9 kW (115 HP) | 85,9 kW (115 HP) | 85,9 kW (115 HP) | 85,9 kW (115 HP) | 85,9 kW (115 HP) | 100 kW (134 HP) | 100 kW (134 HP) | 100 kW (134 HP) |
| 27 km/h (16,8 mph) | 27 km/h (16,8 mph) | 27 km/h (16,8 mph) | 27 km/h (16,8 mph) | 27 km/h (16,8 mph) | 27 km/h (16,8 mph) | 27 km/h (16,8 mph) | 27 km/h (16,8 mph) | 27 km/h (16,8 mph) | 27 km/h (16,8 mph) | 27 km/h (16,8 mph) |
| 270 L (71,3 gal) | - | 500 L (132,09 gal) | - | 500 L (132,09 gal) | 600 L (158,5 gal) | - | 600 L (158,5 gal) | 600 L (158,5 gal) | - | 600 L (158,5 gal) |
| 1,7 m³ (60 ft³) | 1,7 m³ (60 ft³) | 2,5 m³ (88 ft³) | 2,5 m³ (88 ft³) | 2,5 m³ (88 ft³) | 3,5 m³ (124 ft³) | 3,5 m³ (124 ft³) | 3,5 m³ (124 ft³) | 5,0 m³ (177 ft³) | 5,0 m³ (177 ft³) | 5,0 m³ (177 ft³) |
| 4495 mm (177 in) | 4400 mm (173,2 in) | 5030 mm (198 in) | 4955 mm (195,1 in) | 5030 mm (198 in) | 5290 mm (208,3 in) | 5290 mm (208,3 in) | 5290 mm (208,3 in) | 6100 mm (240,2 in) | 6100 mm (240,2 in) | 6475 mm (254,9 in) |
| 1960 mm (77,2 in) | 1960 mm (77,2 in) | 2370 mm (93,3 in) | 2370 mm (93,3 in) | 2370 mm (93,3 in) | 2400 mm (94,5 in) | 2400 mm (94,5 in) | 2400 mm (94,5 in) | 2370 mm (93,3 in) | 2370 mm (93,3 in) | 2370 mm (93,3 in) |
| 2620 mm (103,1 in) | 2620 mm (103,1 in) | 2915 mm (114,8 in) | 2880 mm (113,4 in) | 2880 mm (113,4 in) | 3140 mm (123,6 in) | 3140 mm (123,6 in) | 3140 mm (123,6 in) | 3040 mm (119,7 in) | 3040 mm (119,7 in) | 3040 mm (119,7 in) |
| 4000 kg (8818 lb) | 4000 kg (8818 lb) | 5900 kg (13007 lb) | 5900 kg (13007 lb) | 5900 kg (13007 lb) | 6700 kg (14771 lb) | 6400 kg (14110 lb) | 6700 kg (14771 lb) | 7400 kg (16314 lb) | 7400 kg (16314 lb) | 7400 kg (16314 lb) |
| 10,5x18" | 10,5x18" | 12,5x18" | 12,5x18" | 12,5x18" | 405/70x20" | 405/70x20" | 405/70x20" | 405/70R24" | 405/70R24" | 405/70R24" |

| DUMPER 1000 F | DUMPER 1000 T | DUMPER 1000 PA | DUMPER 8000 |
|--------------------|--------------------|--------------------|---------------------|
| Lombardini | Lombardini | Lombardini | FPT |
| 15 kW (20 HP) | 15 kW (20 HP) | 15 kW (20 HP) | 125 kW (168 HP) |
| 23 km/h (14,3 mph) | 23 km/h (14,3 mph) | 23 km/h (14,3 mph) | 30 km/h (18,6 mph) |
| 2500 kg (5512 lb) | 2500 kg (5512 lb) | 1120 kg (2469 lb) | 14000 kg (30865 lb) |
| 1,0 m³ (35 ft³) | 1,0 m³ (35 ft³) | 1,0 m³ (35 ft³) | 8,00 m³ (283 ft³) |
| 1,2 m³ (42 ft³) | 1,2 m³ (42 ft³) | 1,2 m³ (42 ft³) | 8,50 m³ (300 ft³) |
| 1300 kg (2866 lb) | 1300 kg (2866 lb) | 1650 kg (3638 lb) | 8430 kg (18585 lb) |
| 3100 mm (122 in) | 3100 mm (122 in) | 4020 mm (158,3 in) | 5841 mm (230 in) |
| 1600 mm (63 in) | 1600 mm (63 in) | 1600 mm (63 in) | 2380 mm (93,7 in) |
| 2520 mm (99,2 in) | 2520 mm (99,2 in) | 2100 mm (82,7 in) | 3160 mm (124,4 in) |
| 7,5x16" | 7,5x16" | 7,5x16" | 12,00 - 24" |

ROTATIVE HANDLERS



| PEGASUS 38.16 - 400" | PEGASUS 40.18 - 400" | PEGASUS 40.25 | PEGASUS 50.19 | PEGASUS 50.21 | PEGASUS 60.16 | PEGASUS 45.30 | PEGASUS 50.26 |
|----------------------|----------------------|---------------------|---------------------|---------------------|---------------------|---------------------|---------------------|
| Kubota | Kubota | FPT | FPT | FPT | FPT | FPT | FPT |
| 73,4 kW (98 HP) | 73,4 kW (98 HP) | 96 kW (129 HP) | 96 kW (129 HP) | 96 kW (129 HP) | 96 kW (129 HP) | 125 kW (168 HP) | 125 kW (168 HP) |
| 26 km/h (16,2 mph) | 26 km/h (16,2 mph) | 40 km/h (24,9 mph) | 40 km/h (24,9 mph) | 40 km/h (24,9 mph) | 40 km/h (24,9 mph) | 40 km/h (24,9 mph) | 40 km/h (24,9 mph) |
| 3800 kg (8378 lb) | 4000 kg (8818 lb) | 4000 kg (8818 lb) | 5000 kg (11023 lb) | 5000 kg (11023 lb) | 6000 kg (13228 lb) | 4900 kg (9921 lb) | 5000 kg (11023 lb) |
| 15,70 m (51,5 ft) | 18,00 m (59,1 ft) | 24,10 m (79,1 ft) | 18,70 m (61,4 ft) | 20,50 m (67,3 ft) | 15,70 m (51,5 ft) | 25,60 m (84,3 ft) | 25,7 m (84,3 ft) |
| 6740 mm (265,4 in) | 6630 mm (261 in) | 8000 mm (315 in) | 6800 mm (267,7 in) | 7150 mm (281,5 in) | 6720 mm (264,6 in) | 8400 mm (330,7 in) | 8409 mm (331,1 in) |
| 2380 mm (93,7 in) | 2380 mm (93,7 in) | 2380 mm (93,7 in) | 2380 mm (93,7 in) | 2380 mm (93,7 in) | 2380 mm (93,7 in) | 2500 mm (98,4 in) | 2500 mm (98,4 in) |
| 3035 mm (119,5 in) | 3035 mm (119,5 in) | 3020 mm (118,9 in) | 3020 mm (118,9 in) | 3020 mm (118,9 in) | 3020 mm (118,9 in) | 3095 mm (121,9 in) | 3095 mm (121,9 in) |
| 13200 kg (29101 lb) | 13700 kg (30203 lb) | 17500 kg (38581 lb) | 16500 kg (36376 lb) | 17500 kg (38669 lb) | 16600 kg (36597 lb) | 22150 kg (48832 lb) | 21000 kg (46297 lb) |
| 400/70x20" | 400/70x20" | 18R22,5" | 18R22,5" | 18R22,5" | 18R22,5" | 18R22,5" | 18R22,5" |

HEAVY DUTY



| HERCULES 100.10 | HERCULES 120.10 | HERCULES 190.10 | HERCULES 210.10 | HERCULES 230.10 |
|---------------------|---------------------|---------------------|---------------------|---------------------|
| FPT | FPT | FPT | FPT | FPT |
| 125 kW (168 HP) | 125 kW (168 HP) | 125 kW (168 HP) | 125 kW (168 HP) | 125 kW (168 HP) |
| 35 km/h (21,7 mph) | 35 km/h (21,7 mph) | 23 km/h (14,3 mph) | 23 km/h (14,3 mph) | 22 km/h (13,7 mph) |
| 10000 kg (22046 lb) | 12000 kg (26455 lb) | 19000 kg (41888 lb) | 21000 kg (46297 lb) | 23000 kg (50706 lb) |
| 9,50 m (31,2 ft) | 9,50 m (31,2 ft) | 10,20 m (33,5 ft) | 10,20 m (33,5 ft) | 10,15 m (33,3 ft) |
| 6050 mm (238,2 in) | 6050 mm (238,2 in) | 6800 mm (267,7 in) | 6800 mm (267,7 in) | 6800 mm (267,7 in) |
| 2420 mm (95,3 in) | 2420 mm (95,3 in) | 2600 mm (102,4 in) | 2700 mm (106,3 in) | 2880 mm (113,4 in) |
| 2890 mm (113,8 in) | 2890 mm (113,8 in) | 2930 mm (115,4 in) | 2930 mm (115,4 in) | 2980 mm (117,3 in) |
| 16000 kg (35274 lb) | 16800 kg (37038 lb) | 24500 kg (54013 lb) | 27500 kg (60627 lb) | 29450 kg (64926 lb) |
| 17,5x25" | 17,5x25" | 20,5R25" | 23,5R25" | 26,5R25" |

* riferita a ruote con diametro massimo ammesso - * referred to wheels having the maximum allowable diameter - * en référence à des roues ayant un diamètre maximum admis * referida a ruedas con un diámetro máximo admitido - * in Bezug auf Reifen mit maximal zulässigem Durchmesser - * Odnosi się do kół o maksymalnej dopuszczalnej średnicy - * Referente às rodas com diâmetro máximo admitido - * относится к колесам с максимальным допустимым диаметром